BUILD YOUR BRIDGE TO SUCCESS
ACCURIOPRESS C4080 / C4070

RETHINK VERSATILITY

Introducing the AccurioPress C4080 / C4070 – the incredibly versatile digital printer that connects you with success. With enhanced finishing, intelligent automation, flawless quality and advanced capabilities, simply build your perfect configuration from a huge range of innovative possibilities and say yes to more opportunities that will grow your business.

ACCURIOPRESS C4080 / C4070
SPECIFICATIONS
RETHINK OPTIONS

SYSTEM SPECIFICATIONS

Resolution	3,600 (equivalent) x 2,400 dpi x 8 bit
Paper weight	62 – 360 g/m2
Paper sizes	330.2 x 487.7 mm
	330.2 x 862 mm (max.duplex)
	330.2 x 1300 mm (max. simplex)
Paper input	Max.: 15,390 sheets
Dimension (WxDxH)	31.49'' x 35.55'' x 42.36''
Unit weight	696.66 lb.

PRODUCTIVITY

AccurioPress C4080	
8.5 x 11 – max. per minute	80 ppm
11 x 17 – max. per minute	44 ppm
AccurioPress C4070	
8.5 x 11 – max. per minute	70 ppm
11 x 17 – max. per minute	38 ppm

KONICA MINOLTA IMAGE CONTROLLER IC-609

Architecture	Internal
OS	Linux
CPU	Intel Core i5 6500
Clock speed	3.2 GHz
RAM std	16 GB
HDD	2 TB (2 x 1TB)
Page-description language	Adobe PostSript 3; PDF v1.7; APPE v4.6 (with UK-220); TIFF (v6); PPML v2.2
Applicable OS	Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11–14

FIERY IMAGE CONTROLLER IC-317

Architecture	External
OS	Windows 10
CPU	Intel® CoreTM I5-6500 processor
Clock speed	3.2 GHz up to 3.6 GHz Turbo
RAM std	8 GB
HDD	1 TB
Page-description language	Adobe® PostScript® Levels 1, 2, 3, APPE 5, PDF/X-1a, 3, and 4, EPS, Microsoft Office document formats: doc, docx, xls, xlsx, ppt, pptx, pub (via Hot Folders), JPEG, 1-bit TIFF, TIFF (optional via Graphic Arts Pro Package), Fiery FreeForm™ Plus, PPML v3.0, PDF/VT 1 & 2, Creo VPS
Applicable OS	Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11–14

FIERY IMAGE CONTROLLER IC-419

Architecture	Internal
OS	Linux
CPU	Intel® Pentium® Processor G4400
Clock speed	3.3 GHz
RAM std	8 GB
HDD	500 GB
Page-description language	Adobe® PostScript® Levels 1, 2, 3, APPE 5, Microsoft Office document formats: doc, docx, xls, xlsx, ppt, pptx, pub (via Hot Folders)
Applicable OS	Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11–14

OPTIONS

KM Image Controller	IC-609
EFI external Controller	IC-317
EFI internal Controller	IC-419
Paper Feeding Unit	PF-602m
Dehumidifier heater	HT-504
Paper feeding unit	PF-707m
Dehumidifier heater	HT-506
PFU connection Kit	FA-502
Large capacity feeding unit	LU-202m
Dehumidifier heater f. LU	HT-503
Envelop printing guidef. LU	MK-746
Large capacity feeding unit (banner)	LU-202XLm
Multi bypass feeding	MB-508
Banner Paper Feeder kit	MK-760
Multi bypass tray	MB-509
Intelligent Media Sensor	IM-101
Output Tray	OT-511
Relay Unit	RU-518m
Humidifier	HM-103
Intelligent Quality Optimizer	IQ-501
Purge Unit	RU-702
Auto Inspection Unit	UK-301
Envelop Fusing Unit	EF-107
Long Sheet Kit (Output)	MK-761
Trimmer Unit	TU-510
Creasing kit (Downwards)	CR-102
Creasing kit (Upwards)	CR-103
Center Slit kit	TU-504
CD Perforation kit	PE-102
FD Perforation kit	PE-103
Banner paper kit	MK-764
Business Card kit	JS-507
Folding and Punching Unit	FD-503
Stacking Unit	LS-507
Handcart	LC-502
Booklet Making Unit	SD-506
Booklet Making Unit	SD-513
Square Folding Kit	FD-504
Slitter Kit	TU-503
Creaser Kit	CR-101
Perfect Binding Unit	PB-503
Stapling Unit	FS-532m
Saddle Stitcher Kit	SD-510
Punch Kit	PK-525
Post Inserter Kit	PI-502
Output Tray Unit	OT-512
Long Sheet Kit (Output)	MK-761

– All specifications refer to A4-size paper of 80 gsm quality.

– The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

– The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.

– Some of the product illustrations contain optional accessories.

– Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.

– Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.

– All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.